

3. Specifications

3.1 CU-2Z35TBE

Item			Unit	OUTDOOR UNIT
Indoor Unit Combination				1.6kW + 2.0kW
Power Source				1 Phase, 230V, 50Hz (Power supply from outdoor unit)
Cooling Operation	Capacity		kW	3.5 (1.50 ~ 4.50)
			BTU/h	11900 (5120 ~ 15300)
	Electrical Data	Running Current	A	3.35
		Power Input	kW	0.72 (0.25 ~ 1.10)
		EER	W/W	4.86 (6.00 ~ 4.09)
	Annual Energy Consumption (AEC)		kWh	360
	Annual Consumption		kWh	144
	Noise	Sound Pressure Level	dB-A (H/L)	48 / -
		Sound Power Level	dB (H/L)	63 / -
Heating Operation	Capacity		kW	4.20 (1.1 ~ 5.60)
			BTU/h	14300 (3750 ~ 19100)
	Electrical Data	Running Current	A	4.0
		Power Input	kW	0.86 (0.21 ~ 1.34)
		COP	W/W	4.88 (5.24 ~ 4.18)
	Annual Consumption		kWh	974
	Noise	Sound Pressure Level	dB-A (H/L)	50 / -
		Sound Power Level	dB (H/L)	65 / -
	Maximum Current			A
Maximum Input Power			W	2.39k
Starting Current			A	4.00
Dimension	Height		mm	619
	Width		mm	824 (+70)
	Depth		mm	299
Net Weight			kg	39
Pipe Length Range (1 room)			m	3 ~ 20
Maximum Pipe Length (Total Room)			m	30
Piping	Standard Length		m	5
	Height Difference		m	10
	Add. Gas Amount		g/m	15
	Pipe Length for Add. Gas		m	20
Refrigerant Pipe Diameter	Liquid Side		mm (inch)	6.35 (1/4)
	Gas Side		mm (inch)	9.52 (3/8)
Compressor	Type			Hermetic Motor / Rotary
	Motor Type			Brushless (4-poles)
	Rated Output		W	900
Fan Motor	Type			Propeller Fan
	Motor Type			DC Motor (8-poles)
	Rated Output		W	40
Fan Speed	High (Cooling / Heating)		RPM	700 / 930

Item			Unit	OUTDOOR UNIT	
Heat Exchanger	Type			Plate fin configuration forced draft type	
	Tube Material			Copper	
	Fin Material			Aluminum (Pre Coat)	
	Row / Stage			2 / 28	
	FPI			17	
Air Volume	High (Cooling / Heating)		m ³ /min (ft ³ /mm)	28.5 (1005) / 36.9 (1305)	
Refrigerant Control Device				Expansion Valve	
Refrigerant Oil			cm ³	FW50S (450)	
Refrigerant (R32)			g	1.12k	
				Dry Bulb	Wet Bulb
Outdoor Operation Range	Cooling	Maximum	°C	46	26
		Minimum	°C	-10	—
	Heating	Maximum	°C	24	18
		Minimum	°C	-15	-16

Note

- Specifications are subject to change without notice for further improvement.

3.2 CU-2Z41TBE

Item			Unit	OUTDOOR UNIT
Indoor Unit Combination				1.6kW + 2.5kW
Power Source				1 Phase, 230V, 50Hz (Power supply from outdoor unit)
Cooling Operation	Capacity		kW	4.1 (1.5 ~ 5.2)
			BTU/h	14000 (5120 ~ 17700)
	Electrical Data	Running Current	A	4.15
		Power Input	kW	0.90 (0.25 ~ 1.37)
		EER	W/W	4.56 (6.00 ~ 3.80)
	Annual Energy Consumption (A.E.C)		kWh	450
	Annual Consumption		kWh	169
	Noise	Sound Pressure Level	dB-A (H/L)	48 / -
		Sound Power Level	dB (H/L)	63 / -
Heating Operation	Capacity		kW	4.6 (1.1 ~ 7.0)
			BTU/h	15700 (3750 ~ 23900)
	Electrical Data	Running Current	A	4.45
		Power Input	kW	0.96 (0.21 ~ 1.79)
		COP	W/W	4.79 (5.24 ~ 3.91)
	Annual Consumption		kWh	1065
	Noise	Sound Pressure Level	dB-A (H/L)	50 / -
		Sound Power Level	dB (H/L)	65 / -
	Maximum Current			A
Maximum Input Power			W	2.50k
Starting Current			A	4.45
Dimension	Height		mm	619
	Width		mm	824 (+70)
	Depth		mm	299
Net Weight			kg	39
Pipe Length Range (1 room)			m	3 ~ 20
Maximum Pipe Length (Total Room)			m	30
Piping	Standard Length		m	5
	Height Difference		m	10
	Add. Gas Amount		g/m	15
	Pipe Length for Add. Gas		m	20
Refrigerant Pipe Diameter	Liquid Side		mm (inch)	6.35 (1/4)
	Gas Side		mm (inch)	9.52 (3/8)
Compressor	Type			Hermetic Motor / Rotary
	Motor Type			Brushless (4-poles)
	Rated Output		W	900
Fan Motor	Type			Propeller Fan
	Motor Type			DC Motor (8-poles)
	Rated Output		W	40
Fan Speed	High (Cooling / Heating)		RPM	800 / 930
Heat Exchanger	Type			Plate fin configuration forced draft type
	Tube Material			Copper
	Fin Material			Aluminum (Pre Coat)
	Row / Stage			2 / 28
	FPI			17

Item			Unit	OUTDOOR UNIT	
Air Volume	High (Cooling / Heating)		m ³ /min (ft ³ /mm)	32.7 (1155) / 36.9 (1305)	
Refrigerant Control Device				Expansion Valve	
Refrigerant Oil			cm ³	FW50S (450)	
Refrigerant (R32)			g	1.12k	
				Dry Bulb	Wet Bulb
Outdoor Operation Range	Cooling	Maximum	°C	46	26
		Minimum	°C	-10	—
	Heating	Maximum	°C	24	18
		Minimum	°C	-15	-16

Note

- Specifications are subject to change without notice for further improvement.

3.3 CU-2Z50TBE

Item			Unit	OUTDOOR UNIT
Indoor Unit Combination				2.0kW + 2.5kW
Power Source				1 Phase, 230V, 50Hz (Power supply from outdoor unit)
Cooling Operation	Capacity		kW	5.0 (1.5 ~ 5.4)
			BTU/h	17100 (5120 ~ 18400)
	Electrical Data	Running Current	A	5.35
		Power Input	kW	1.18 (0.25 ~ 1.49)
		EER	W/W	4.24 (6.00 ~ 3.62)
	Annual Energy Consumption (A.E.C)		kWh	590
	Annual Consumption		kWh	206
	Noise	Sound Pressure Level	dB-A (H/L)	50 / -
		Sound Power Level	dB (H/L)	65 / -
Heating Operation	Capacity		kW	5.6 (1.1 ~ 7.2)
			BTU/h	19100 (3750 ~ 24600)
	Electrical Data	Running Current	A	5.50
		Power Input	kW	1.21 (0.21 ~ 1.80)
		COP	W/W	4.63 (5.24 ~ 4.00)
	Annual Consumption		kWh	1278
	Noise	Sound Pressure Level	dB-A (H/L)	52 / -
		Sound Power Level	dB (H/L)	67 / -
	Maximum Current			A
Maximum Input Power			W	2.62k
Starting Current			A	5.5
Dimension	Height		mm	619
	Width		mm	824 (+70)
	Depth		mm	299
Net Weight			kg	39
Pipe Length Range (1 room)			m	3 ~ 20
Maximum Pipe Length (Total Room)			m	30
Piping	Standard Length		m	5
	Height Difference		m	10
	Add. Gas Amount		g/m	15
	Pipe Length for Add. Gas		m	20
Refrigerant Pipe Diameter	Liquid Side		mm (inch)	6.35 (1/4)
	Gas Side		mm (inch)	9.52 (3/8)
Compressor	Type			Hermetic Motor / Rotary
	Motor Type			Brushless (4-poles)
	Rated Output		W	900
Air Circulation	Type			Propeller Fan
	Motor Type			DC Motor (8-poles)
	Rated Output		W	40
Fan Speed	High (Cooling / Heating)		RPM	900 / 1000
Heat Exchanger	Type			Plate fin configuration forced draft type
	Tube Material			Copper
	Fin Material			Aluminum (Pre Coat)
	Row / Stage			2 / 18
	FPI			17

Item			Unit	OUTDOOR UNIT	
Air Volume	High (Cooling / Heating)		m ³ /min (ft ³ /mm)	36.9 (1305) / 41.1 (1450)	
Refrigerant Control Device				Expansion Valve	
Refrigerant Oil			cm ³	FW50S (450)	
Refrigerant (R32)			g	1.12k	
				Dry Bulb	Wet Bulb
Outdoor Operation Range	Cooling	Maximum	°C	46	26
		Minimum	°C	-10	—
	Heating	Maximum	°C	24	18
		Minimum	°C	-15	-16

Note

- Specifications are subject to change without notice for further improvement.

3. Specifications

3.1 CU-3Z52TBE

Item			Unit	OUTDOOR UNIT
Indoor Unit Combination				1.6kW + 1.6kW + 2.0kW
Power Source				1 Phase, 230V, 50Hz (Power supply from outdoor unit)
Cooling Operation	Capacity		kW	5.20 (1.80 ~ 7.30)
			BTU/h	17700 (6140 ~ 24900)
	Electrical Data	Running Current	A	5.00
		Power Input	W	1.09k (360 ~ 2.18k)
		EER	W/W	4.77 (5.00 ~ 3.35)
	Annual Consumption		kWh	214
	Noise	Sound Pressure Level	dB-A (H/L)	47 / -
		Sound Power Level	dB (H/L)	61 / -
Heating Operation	Capacity		kW	6.80 (1.60 ~ 8.30)
			BTU/h	23200 (5460 ~ 28300)
	Electrical Data	Running Current	A	6.70
		Power Input	W	1.47k (320 ~ 2.17k)
		COP	W/W	4.63 (5.00 ~ 3.82)
	Annual Consumption		kWh	1667
	Noise	Sound Pressure Level	dB-A (H/L)	48 / -
		Sound Power Level	dB (H/L)	62 / -
Maximum Current			A	15.2
Maximum Input Power			W	3.46k
Starting Current			A	6.70
Extra Low Temperature	Capacity		kW	3.95
	Input Power		W	1470
	Cop		W/W	2.69
Dimension	Height		mm	795
	Width		mm	875 (+95)
	Depth		mm	320
Net Weight			kg	71
Pipe Length Range (1 room)			m	3 ~ 25
Maximum Pipe Length (Total Room)			m	50
Piping	Standard Length		m	5
	Height Difference		m	15
	Add. Gas Amount		g/m	20
	Pipe Length for Add. Gas		m	30
Refrigerant Pipe Diameter	Liquid Side		mm (inch)	6.35 (1/4)
	Gas Side		mm (inch)	9.52 (3/8)
Compressor	Type			Hermetic Motor / Rotary
	Motor Type			Brushless (4-poles)
	Rated Output		W	1.30k
Fan Motor	Type			Propeller Fan
	Motor Type			DC Motor (8-poles)
	Rated Output		W	60
Fan Speed	High (Cooling / Heating)		RPM	620 / 580

Item			Unit	OUTDOOR UNIT	
Heat Exchanger	Type			Plate fin configuration forced draft type	
	Tube Material			Copper	
	Fin Material			Aluminum (Pre Coat)	
	Row / Stage			2 / 36	
	FPI			19	
Air Volume	High (Cooling / Heating)		m ³ /min (ft ³ /min)	41.7 (1470) / 41.7 (1470)	
Refrigerant Control Device			min	Expansion Valve	
Refrigerant Oil			cm ³	FW50S (900)	
Refrigerant (R32)			g	2.10k	
				Dry Bulb	Wet Bulb
Outdoor Operation Range	Cooling	Maximum	°C	46	26
		Minimum	°C	-10	—
	Heating	Maximum	°C	24	18
		Minimum	°C	-15	-16

Note

- Specifications are subject to change without notice for further improvement.

3.2 CU-3Z68TBE

Item			Unit	OUTDOOR UNIT
Indoor Unit Combination				1.6kW + 2.0kW + 3.5kW
Power Source				1 Phase, 230V, 50Hz (Power supply from outdoor unit)
Cooling Operation	Capacity		kW	6.8 (1.90 ~ 8.00)
			BTU/h	23200 (6480 ~ 27300)
	Electrical Data	Running Current	A	8.40
		Power Input	W	1.86k (270 ~ 2.37k)
		EER	W/W	3.66 (7.04 ~ 3.38)
	Annual Consumption		kWh	298
	Noise	Sound Pressure Level	dB-A (H/L)	51 / -
		Sound Power Level	dB (H/L)	65 / -
Heating Operation	Capacity		kW	8.5 (3.30 ~ 10.40)
			BTU/h	29000 (11300 ~ 35500)
	Electrical Data	Running Current	A	9.7
		Power Input	W	2.15k (620 ~ 2.86k)
		COP	W/W	3.95 (5.32 ~ 3.64)
	Annual Consumption		kWh	1733
	Noise	Sound Pressure Level	dB-A (H/L)	52 / -
		Sound Power Level	dB (H/L)	66 / -
Maximum Current			A	15.6
Starting Current			A	9.70
Maximum Input Power			W	3.55k
Extra Low Temperature	Capacity		kW	4.45
	Input Power		W	2450
	COP		W/W	1.82
Dimension	Height		mm	795
	Width		mm	875 (+95)
	Depth		mm	320
Net Weight			kg	71
Pipe Length Range (1 room)			m	3 ~ 25
Maximum Pipe Length (Total Room)			m	60
Piping	Standard Length		m	5
	Height Difference		m	15
	Add. Gas Amount		g/m	20
	Pipe Length for Add. Gas		m	30
Refrigerant Pipe Diameter	Liquid Side		mm (inch)	6.35 (1/4)
	Gas Side		mm (inch)	9.52 (3/8)
Compressor	Type			Hermetic Motor / Rotary
	Motor Type			Brushless (4-poles)
	Rated Output		W	1.30k
Fan Motor	Type			Propeller Fan
	Motor Type			DC Motor (8-poles)
	Rated Output		W	60
Fan Speed	High (Cooling / Heating)		RPM	600 / 680

Item			Unit	OUTDOOR UNIT	
Heat Exchanger	Type			Plate fin configuration forced draft type	
	Tube Material			Copper	
	Fin Material			Aluminum (Pre Coat)	
	Row / Stage			2 / 36	
	FPI			19	
Air Volume	High (Cooling / Heating)		m ³ /min (ft ³ /min)	42.5 (1500) / 49.4 (1745)	
Refrigerant Control Device			min	Expansion Valve	
Refrigerant Oil			cm ³	FW50S (900)	
Refrigerant (R32)			g	2.10k	
				Dry Bulb	Wet Bulb
Outdoor Operation Range	Cooling	Maximum	°C	46	26
		Minimum	°C	-10	—
	Heating	Maximum	°C	24	18
		Minimum	°C	-15	-16

Note

- Specifications are subject to change without notice for further improvement.

3.3 CU-4Z68TBE

Item			Unit	OUTDOOR UNIT
Indoor Unit Combination				1.6kW + 1.6kW + 1.6kW + 2.0kW
Power Source				1 Phase, 230V, 50Hz (Power supply from outdoor unit)
Cooling Operation	Capacity		kW	6.80 (1.90 ~ 8.80)
			BTU/h	23200 (6480 ~ 30000)
	Electrical Data	Running Current	A	7.00
		Power Input	W	1.55k (340 ~ 2.47k)
		EER	W/W	4.39 (5.59 ~ 3.56)
	Annual Consumption		kWh	298
	Noise	Sound Pressure Level	dB-A (H/L)	49 / -
		Sound Power Level	dB (H/L)	63 / -
Heating Operation	Capacity		kW	8.50 (3.00 ~ 10.60)
			BTU/h	29000 (36100 ~ 10200)
	Electrical Data	Running Current	A	8.60
		Power Input	W	1.90k (580 ~ 2.68k)
		COP	W/W	4.47 (5.17 ~ 3.96)
	Annual Consumption		kWh	1933
	Noise	Sound Pressure Level	dB-A (H/L)	50 / -
		Sound Power Level	dB (H/L)	64 / -
Maximum Current			A	15.6
Maximum Input Power			W	3.55k
Starting Current			A	8.60
Extra Low Temperature	Capacity		kW	4.45
	Input Power		W	2230
	Cop		W/W	2.00
Dimension	Height		mm	795
	Width		mm	875 (+95)
	Depth		mm	320
Net Weight			kg	72
Pipe Length Range (1 room)			m	3 ~ 25
Maximum Pipe Length (Total Room)			m	60
Piping	Standard Length		m	5
	Height Difference		m	15
	Add. Gas Amount		g/m	20
	Pipe Length for Add. Gas		m	30
Refrigerant Pipe Diameter	Liquid Side		mm (inch)	6.35 (1/4)
	Gas Side		mm (inch)	9.52 (3/8)
Compressor	Type			Hermetic Motor / Rotary
	Motor Type			Brushless (4-poles)
	Rated Output		W	1.30k
Fan Motor	Type			Propeller Fan
	Motor Type			DC Motor (8-poles)
	Rated Output		W	60
Fan Speed	High (Cooling / Heating)		RPM	600 / 620

Item			Unit	OUTDOOR UNIT	
Heat Exchanger	Type			Plate fin configuration forced draft type	
	Tube Material			Copper	
	Fin Material			Aluminum (Pre Coat)	
	Row / Stage			2 / 36	
	FPI			19	
Air Volume	High (Cooling / Heating)		m ³ /min (ft ³ /min)	42.5 (1500) / 44.1 (1555)	
Refrigerant Control Device			min	Expansion Valve	
Refrigerant Oil			cm ³	FW50S (900)	
Refrigerant (R32)			g	2.10k	
				Dry Bulb	Wet Bulb
Outdoor Operation Range	Cooling	Maximum	°C	46	26
		Minimum	°C	-10	—
	Heating	Maximum	°C	24	18
		Minimum	°C	-15	-16

Note

- Specifications are subject to change without notice for further improvement.

3. Specifications

3.1 CU-4Z80TBE

Item				Unit	OUTDOOR UNIT
Indoor Unit Combination					2.0kW + 2.0kW + 2.0kW + 2.0kW
Power Source					1 Phase, 230V, 50Hz (Power supply from outdoor unit)
Cooling Operation	Capacity			kW	8.0 (3.0 ~ 9.2)
				BTU/h	27300 (10200 ~ 31400)
	Electrical Data	Running Current		A	9.5
		Power Input		kW	1.98 (0.53 ~ 2.87)
		EER		W/W	4.04 (5.66 ~ 3.21)
		ERP	Pdesign	kW	8.0
			SEER	W/W	7.9
			Annual Consumption	kWh	354
		Power Factor		%	91
	Noise		Sound Pressure Level	dB-A (H/L)	50 / -
		Sound Power Level	dB (H/L)	67 / -	
Heating Operation	Capacity			kW	9.4 (4.2 ~ 10.6)
				BTU/h	32100 (14300 ~ 36100)
	Electrical Data	Running Current		A	9.5
		Power Input		kW	2.03 (0.70 ~ 3.06)
		EER		W/W	4.63 (6.00 ~ 3.46)
		ERP	Pdesign	kW	6.8
			SCOP	W/W	4.7
			Annual Consumption	kWh	2026
		Power Factor		%	93
	Noise		Sound Pressure Level	dB-A (H/L)	52 / -
		Sound Power Level	dB (H/L)	68 / -	
Maximum Current				A	19.0
Maximum Input Power				kW	4.33
Starting Current				A	9.5
Circuit Breaker Capacity				A	20
Dimension	Height			mm	999
	Width			mm	940
	Depth			mm	340
Net Weight				kg	80
Connection Cable					4 x Ø1.5mm²
Pipe Length Range (1 room)				m	3 ~ 25
Maximum Pipe Length (Total Room)				m	70
Refrigerant Pipe Diameter	Liquid Side			mm (inch)	6.35 (1/4)
	Gas Side			mm (inch)	9.52 (3/8) [Z71TK : 12.7 (1/2)]
Compressor	Type				Hermetic Motor / Rotary
	Motor Type				Brushless (4-poles)
	Rated Output			W	1.70k
Fan Motor	Type				Propeller Fan
	Motor Type				DC Motor (8-poles)
	Rated Output			W	90

Item			Unit	OUTDOOR UNIT	
Fan Speed	High (Cooling / Heating)		RPM	600 / 600	
Heat Exchanger	Type			Plate fin configuration forced draft type	
	Tube Material			Copper	
	Fin Material			Aluminum (Pre Coat)	
	Row / Stage			2 / 46	
	FPI			19	
Air Volume	High (Cooling / Heating)		m ³ /min (ft ³ /min)	50.4 (1780) / 55.6 (1960)	
Refrigerant Control Device				Expansion Valve	
Refrigerant Oil				FW50S (900cm ³)	
Refrigerant (R32)			g	2.72k	
				Dry Bulb	Wet Bulb
Indoor Operation Range	Cooling	Maximum	°C (°F)	32 (89.6)	23 (73.4)
		Minimum	°C (°F)	16 (60.8)	11 (51.8)
	Heating	Maximum	°C (°F)	30 (86.0)	-
		Minimum	°C (°F)	16 (60.8)	-
Indoor Operation Range	Cooling	Maximum	°C (°F)	46 (114.8)	26 (78.8)
		Minimum	°C (°F)	-10 (14.0)	-
	Heating	Maximum	°C (°F)	24 (75.2)	18 (64.4)
		Minimum	°C (°F)	-15 (5.0)	-16 (3.2)

Note

- Specifications are subject to change without notice for further improvement.

3.2 CU-5Z90TBE

Item				Unit	OUTDOOR UNIT
Indoor Unit Combination					1.6kW + 1.6kW + 1.6kW + 1.6kW + 2.5kW
Power Source					1 Phase, 230V, 50Hz (Power supply from outdoor unit)
Cooling Operation	Capacity			kW	9.0 (2.9 ~ 11.5)
				BTU/h	30700 (9890 ~ 39200)
	Electrical Data	Running Current		A	10.5
		Power Input		kW	2.20 (0.55 ~ 3.86)
		EER		W/W	4.09 (5.27 ~ 2.98)
		ERP	Pdesign	kW	9.0
			SEER	W/W	8.5
			Annual Consumption	kWh	371
		Power Factor		%	91
	Noise		Sound Pressure Level	dB-A (H/L)	53 / -
		Sound Power Level	dB (H/L)	69 / -	
Heating Operation	Capacity			kW	10.4 (3.4 ~ 14.5)
				BTU/h	35500 (11600 ~ 49400)
	Electrical Data	Running Current		A	10.1
		Power Input		kW	2.15 (0.53 ~ 4.24)
		EER		W/W	4.84 (6.42 ~ 3.42)
		ERP	Pdesign	kW	8.5
			SCOP	W/W	4.68
			Annual Consumption	kWh	2543
		Power Factor		%	93
	Noise		Sound Pressure Level	dB-A (H/L)	54 / -
		Sound Power Level	dB (H/L)	70 / -	
Maximum Current				A	21.3
Maximum Input Power				kW	4.84
Starting Current				A	10.5
Circuit Breaker Capacity				A	25
Dimension	Height			mm	999
	Width			mm	940
	Depth			mm	340
Net Weight				kg	81
Connection Cable					4 x Ø1.5mm²
Pipe Length Range (1 room)				m	3 ~ 25
Maximum Pipe Length (Total Room)				m	80
Refrigerant Pipe Diameter	Liquid Side			mm (inch)	6.35 (1/4)
	Gas Side			mm (inch)	9.52 (3/8) [Z71TK : 12.7 (1/2)]
Compressor	Type				Hermetic Motor / Rotary
	Motor Type				Brushless (4-poles)
	Rated Output			W	1.7k
Fan Motor	Type				Propeller Fan
	Motor Type				DC Motor (8-poles)
	Rated Output			W	90

Item			Unit	OUTDOOR UNIT	
Fan Speed	High (Cooling / Heating)		RPM	650 / 740	
Heat Exchanger	Type			Plate fin configuration forced draft type	
	Tube Material			Copper	
	Fin Material			Aluminum (Pre Coat)	
	Row / Stage			2 / 46	
	FPI			19	
Air Volume	High (Cooling / Heating)		m³/min (ft³/min)	60.8 (2145) / 70.1 (2475)	
Refrigerant Control Device				Expansion Valve	
Refrigerant Oil				FW50S (900cm³)	
Refrigerant (R32)			g	2.72k	
				Dry Bulb	Wet Bulb
Indoor Operation Range	Cooling	Maximum	°C (°F)	32 (89.6)	23 (73.4)
		Minimum	°C (°F)	16 (60.8)	11 (51.8)
	Heating	Maximum	°C (°F)	30 (86.0)	-
		Minimum	°C (°F)	16 (60.8)	-
Outdoor Operation Range	Cooling	Maximum	°C (°F)	46 (114.8)	26 (78.8)
		Minimum	°C (°F)	-10 (14.0)	-
	Heating	Maximum	°C (°F)	24 (75.2)	18 (64.4)
		Minimum	°C (°F)	-15 (5.0)	-16 (3.2)

Note

- Specifications are subject to change without notice for further improvement.